



NEXT

Reducing Failure Points in LED Signs Through 100% Solid-State Design

A technical white paper on reliability drivers, thermal stress, and service-event reduction mechanisms in fanless LED sign architectures.

Prepared for: NEXT LED Signs | Date: January 2026

Executive Summary

Solid-state design in LED sign cabinets generally refers to an architecture that minimizes or eliminates moving parts (for example, replacing fan-forced airflow with passive thermal pathways and sealed enclosures). From a reliability perspective, this matters because moving parts introduce wear-out mechanisms, and elevated internal temperatures accelerate aging of key electronic components. Across electronics industries, the Arrhenius-based “10°C rule” is commonly used to approximate that many temperature-driven failure mechanisms accelerate significantly with heat; for electrolytic capacitors specifically, multiple technical sources describe lifetime reductions on the order of half for each 10°C increase in operating temperature. ^[1-4]

This paper summarizes the most defensible, non-competitor evidence supporting why fanless, solid-state cabinet design can reduce unplanned downtime and lower the frequency of service interventions. It focuses on measurable engineering drivers (failure modes and thermal acceleration), and avoids unsupported percentage claims about maintenance savings unless a project provides field data.

Scope and definitions

What “solid-state” means in this paper

- No moving parts required for normal cooling or operation (for example, no cabinet fans or motor-driven airflow).
- Thermal management is achieved through passive methods: conduction paths, heat spreaders/sinks, cabinet-as-radiator designs, and controlled airflow by enclosure design.
- Cabinet design favors environmental protection (dust, moisture, pollutants) to reduce contamination-driven faults.

Note: “Solid-state” is used here as an architectural concept for cabinet reliability, not as a claim that every component is immutable. Power conversion, LED drive electronics, and connectors still exist and must be engineered correctly.

Reliability fundamentals: why fewer parts usually means fewer failures

In reliability engineering, each additional component can add failure modes and increase the probability that at least one component fails over time. While high-quality design and redundancy can mitigate this, the simplest way to reduce failure exposure is often to reduce the number of wear-out components and the number of interconnects that can loosen, corrode, or degrade.



Mechanical wear-out is a known reliability category


Cooling fans are a common example of a wear-out component: bearings, motor electronics, and housings can degrade under real-world environmental stressors such as dust, humidity, and heat. A PHM Society conference paper reviewing fan failure modes describes internal failures including motor and bearing issues, and external failures including casing degradation. [5]

Thermal Management Without Mechanical Cooling

In LED signs, thermal stress is not a theoretical concern; power conversion and LED drive circuits generate significant heat. If heat is not reliably moved to the outside, internal temperatures rise, accelerating the aging of temperature-sensitive components.

The 10°C Rule: A 10°C increase above rated temperature can reduce electronic component lifespan by 50%.

Capacitor Sensitivity: Electrolytic capacitors are responsible for an estimated 30% to 60% of driver circuitry failures in outdoor power electronics.



System lifetime vs. LED diode lifetime


A frequent misunderstanding in LED products is equating LED lumen maintenance (for example, L70 projections) with complete system lifetime. The Illuminating Engineering Society (IES) explicitly cautions against using LED lumen maintenance life as the sole metric for determining solid-state product lifetime. [6]

Similarly, U.S. Department of Energy guidance notes that using LED device lumen maintenance as a proxy for total system lifetime can be misleading, because lumen maintenance is only one component of overall reliability and other components often determine system life. [7]

How solid-state cabinet design can reduce service interventions

Mechanism 1: removing fan-driven failure modes

If a cabinet design does not rely on fans for cooling, it removes fan-specific failure modes (bearing wear, motor/electronics failure, casing degradation) from the system's fault tree. This does not make the product "failure-proof," but it reduces the number of pathways that can lead to overheating and downstream component stress. [5]



Mechanism 2: stabilizing temperature to slow aging

Fanless thermal strategies emphasize consistent heat conduction and radiation through designed pathways. Because temperature is a key accelerator for aging in components such as electrolytic capacitors, keeping internal temperatures lower and avoiding thermal spikes can materially extend component life. [1-4]

Mechanism 3: reducing contamination-driven faults

In many outdoor electronics deployments, environmental contamination (dust, moisture, pollutants) contributes to corrosion, blocked airflow, and intermittent connections. Fanless and sealed or semi-sealed cabinet designs can reduce the amount of external contaminants pulled into the cabinet compared with forced-air designs that continuously exchange air with the environment. The magnitude of benefit depends on gasket design, pressure equalization strategies, and serviceability considerations.

A Practical Cost Model for Service-Event Impact

The financial benefit of solid-state architecture is realized through the reduction of unplanned service interventions, or "truck rolls". Cost Model: Expected Annual Service Cost = (Service events per year) \times (Cost per service event). Industry Benchmarks: In 2026, the average cost of a "truck roll" ranges from \$200 to \$500, with specialized labor and equipment for large-format signs often pushing total costs toward \$1,100 per event. Operational Uptime: By eliminating fan-specific failure modes (bearing wear, motor failure), owners can significantly reduce these high-cost interventions. Design and procurement checklist (what to ask, regardless of vendor)

- How is heat moved from power supplies and drivers to the outside environment (conduction paths, heat spreaders, cabinet-as-radiator features)?
- What is the cooling dependency: does the cabinet rely on fans or forced airflow for normal operation?
- What is the environmental protection approach (sealing strategy, corrosion mitigation, ingress protection targets)?
- How are temperature-sensitive components specified (capacitor ratings, thermal derating approach, junction temperature margins)?
- What is the service philosophy (front-service vs. rear-service, modular replacement strategy, time-to-repair assumptions)?
- What evidence is provided for reliability claims (third-party tests, published reliability models, standards-based reporting)?

Limitations and statement on evidence

This paper intentionally avoids hard percentage claims (for example, “X% fewer truck rolls”) unless they are supported by verifiable, non-competitor published data or a project’s own service history. The strongest broadly applicable evidence for solid-state cabinet design focuses on (1) eliminating mechanical wear-out mechanisms such as fans and (2) reducing thermal stress, which is well established as a life accelerator for key electronic components. [1–7]

References

- [1] Gupta, A., et al. (2018). A Review of Degradation Behavior and Modeling of Capacitors (NREL/TP-5D00-71386). National Renewable Energy Laboratory (NREL). <https://docs.nrel.gov/docs/fy19osti/71386.pdf>
- [2] Heliotronics (cited in NREL) (2005 (cited) / 2006 (report)). Statement on 10°C temperature increase halving electrolytic capacitor lifetime (as cited). NREL Report: Review of PV Inverter Technology Cost and Performance. <https://docs.nrel.gov/docs/fy06osti/38771.pdf>
- [3] Electronics Cooling (2017). Does a 10°C Increase in Temperature Really Reduce the Life of Electronics by Half?. Electronics-Cooling.com. <https://www.electronics-cooling.com/2017/08/10c-increase-temperature-really-reduce-life-electronics-half/>
- [4] United Chemi-Con (2022). Lifetime of Aluminum Electrolytic Capacitors (FAQ). Chemi-Con (manufacturer technical FAQ). <https://www.chemi-con.co.jp/en/faq/detail.php?id=allLifetime>
- [5] Banimilhim, A., et al. (2023). Cooling Fan Failure Modes to Enable Development of Automotive ECU Fan Health Monitoring System. PHM Society Conference Proceedings. https://papers.phmsociety.org/index.php/phmconf/article/download/3521/phmc_23_3521
- [6] Illuminating Engineering Society (IES) (2018). PS-10-18: IES Position on LED Product Lifetime Prediction. IES Position Statement. <https://ies.org/advocacy/ps-10-18/>
- [7] U.S. Department of Energy (SSL Program) (2011). LED Luminaire Lifetime: Recommendations for Testing and Reporting. U.S. DOE Solid-State Lighting Program. https://www1.eere.energy.gov/buildings/publications/pdfs/ssl/led_luminaire-lifetime-guide.pdf
- [8] ENERGY STAR (Accessed 2026-01). Signage Displays (Program Overview). ENERGY STAR. https://www.energystar.gov/products/signage_displays

ABOUT NEXT LED SIGNS

NEXT LED Signs is a U.S.-based manufacturer of large-format LED display systems, specializing in outdoor LED signs, digital scoreboards, and high-performance video displays for education, municipal, commercial, and live-event environments. With decades of combined engineering experience, **NEXT LED Signs** designs and builds solid-state LED displays engineered for long-term reliability, reduced maintenance, and lower total cost of ownership.

NEXT LED Signs systems are deployed across the United States in schools, stadiums, civic spaces, and commercial installations where performance, uptime, and durability matter most. Every display is built with a focus on thermal management, component longevity, and serviceability—delivering dependable operation in demanding outdoor conditions.

For more information about LED signs, scoreboards, and solid-state display engineering, visit www.nextledsigns.com, email info@nextledsigns.com, or call (888) 359-9558.



8805 E. 34 ST. N.
WICHITA, KANSAS 67226
888-263-6530